

COMPACT SAFETY LIGHT using energy-saving technology TYPE HA-SKE



Photo: Safety compact light HA-SKEP (Part No.: HA-220301)

Features

- Compact light with flameproof enclosure type of protection
- Energy-saving compact fluorescent lamps with high output of light for a power rating of 3 x 9 W
- Impact-resistant polycarbonate cover and reflector for good illumination of larger areas
- Electronic choke for consistent light output
- Microswitch to turn off at all poles when lamp is opened
- Continues operation with adequate light output even if one compact fluorescent tube fails
- Possible to change separate compact fluorescent tubes
- Optionally with fault location switch and / or shutdown switch
- Plug-in type pressure-resistant cable quick-connectors

Technical Data

- | | |
|--|--------------------|
| • Designed operating voltage ¹⁾ | 127 V ± 20 % |
| • Designed frequency | 50 - 60 Hz |
| • Designed operating current | 125 mA |
| • Power consumption | 28 VA |
| • Power factor | 0.98 |
| • Clampable cable cross-section | 10 mm ² |
| • Ambient temperature | ≤ 40 °C |
| • Weight | ca. 21 kg |
| • Dimensions | |
| - Length | 294 mm |
| - Width | 260 mm |
| - Height | 115 mm |

¹⁾ Also available for 230 V

Types of protection

Type of protection: Ex d I
Level of protection: IP 54

Certification

KDB No. 92.253W of 22.06.92
with appendices